

EL-525X7.9-1606-L128

New Exprience Of Lighting

- Lumileds Luxeon 2835 SA-A1 3V
- Constant Color, MacAdams Step 3
- Homogeneous illumination
- Optional PCB Material Selection



- Substrate:ALU/FR4/CEM1/CEM3
- PCB Thickness:1.0/1.6 mm
- Copper Weight:35Um/70Um
- Surface Treatment:HASL/OSP
- Thermal Conductivity:1W/1.2W/1.5W/2W
- Breakdown Voltage:2000V

Electrical Specification

Product Code	Colour	Luminous Flux TC:25°C Tj:25°C	Forward Voltage Flux Tj:25°C	Serial	Parallel	Power Consumption TC:25°C Tj:25°C	Efficacy TC: 25°C Tj:25°C	CRI
	(k)	(lm)	(v)			(w)	(lm/w)	(Ra)
Operation Mode at 500 mA								
EL-525X7.9-1606-L128-30-80	3000	4030	44.64	16	6	22.32	180.55	80
EL-525X7.9-1606-L128-40-80	4000	4194	44.64	16	6	22.32	187.90	80
EL-525X7.9-1606-L128-65-80	6500	4139	44.64	16	6	22.32	185.43	80
Operation Mode at 700 mA								
EL-525X7.9-1606-L128-30-80	3000	5495	45.6	16	6	31.92	172.14	80
EL-525X7.9-1606-L128-40-80	4000	5693	45.6	16	6	31.92	178.35	80
EL-525X7.9-1606-L128-65-80	6500	5628	45.6	16	6	31.92	176.31	80
Operation Mode at 1000 mA								
EL-525X7.9-1606-L128-30-80	3000	7596	46.88	16	6	46.88	162.03	80
EL-525X7.9-1606-L128-40-80	4000	7828	46.88	16	6	46.88	166.97	80
EL-525X7.9-1606-L128-65-80	6500	7753	46.88	16	6	46.88	165.37	80

**These values are estimated.






EL-525X7.9-1606-L128

Mechanical Specification

New Exprience Of Lighting

PCB Specification


- Length:525 mm
- Width:7.9 mm
- Height:2.25 mm
- Thickness of PCB:1.6 mm



LEDs Specification

- CRI:80
- IF-Type:65 mA
- IF-Max:200 mA
- Tj-Typ(sorting),Tj-Max:45°C-85°C

Connection Diagram




EL-525X7.9-1606-L128

Mechanical Dimensions

New Exprience Of Lighting

View from Front side (Scale 1:1)



View from Bottom side (Scale 1:1)