Protection Devices

ELC-GSPD3

ELC-GSPD3 - Surge Protection Device (10 kV / 20 kV)



ELC-GSPD3 is a surge protection device. Intended for surge protection applications in lighting circuits.

Technical data prepared from the model-specific datasheet.

info@electrio.com.tr +90 545 574 15 19


Technical data

Model code	ELC-GSPD3
Application / option	10 kV / 20 kV
Protection rating	IP67
10 kV - Uc (TUV/CE)	320 VAC / 50 Hz
20 kV - Uc (TUV/CE)	320 VAC / 50 Hz
Input voltage (ETL)	277 VAC / 50 Hz
Maximum continuous operating voltage MCOV	320 V
Open-circuit impulse voltage Uoc	10 kV / 20 kV
10 kV - In / Imax (8/20 µs)	5 kA / 10 kA
20 kV - In / Imax (8/20 µs)	10 kA / 20 kA
10 kV - protection level Up (TUV/CE)	L-N: ≤1.25 kV; L-PE: ≤1.5 kV; N-PE: ≤1.5 kV
20 kV - protection level Up (TUV/CE)	L-N: <1.4 kV; L-PE: <1.5 kV; N-PE: 1.5 kV
Housing characteristic	UL94-V0
Operating temperature	-40 °C ~ +85 °C
Approvals / compliance stated in the source	TUV, ETL, CE, UKCA, CQC, RoHS
Dimensions (reference)	32 × 18 × 32 mm

info@electrio.com.tr +90 545 574 15 19

Technical drawing

ELC-GSPD3



Drawing reproduced from the source document. Dimensions are in mm; refer to the drawing for details and tolerances.

info@electrio.com.tr +90 545 574 15 19